

# TURNING 28 DAYS INTO 48 HOURS



- Save Time
- Save Energy
- High Coverage
- Fire Resistant
- No Shrinkage Cracks
- High Thermal Insulation

30kg

## PROPLASTER™



Revolutionary Product!  
Light Weight Gypsum Wall Plaster

# PROPLASTER™

**ProPlaster™ manufactured from the highest quality gypsum. It is designed for any type of interior wall and ceiling surfaces, providing non-combustibility, directly over porous concrete blocks**

Arish™, ProPlaster™ is gypsum based plaster suitable for application on most internal backgrounds including brick, block and concrete. It consists of Gypsum Hemihydrate, formulated with special additives to enhance working and setting characteristics. It is specially formulated to replace a dirty, time consuming and conventional (sand-cement) plastering methods of interior walls. ProPlaster™ provides smooth, silky white surface ready to receive a decorative finish. It contains light weight aggregates to improve plaster's workability, coverage, application and post usage behavior. ProPlaster can be applied from 8mm to 25mm thick which can be either machine or hand applied, making ideal for any size of commercial or domestic applications.

## Features

- One Coat Putty Application
- No Curing Time Required
- No Primer Required Before Painting
- Save Substantial Time
- Create a Smoother Finish
- Decrease Energy Consumption
- Reduces Echoes And Level Of Noise
- Requires Less Paint

## MIX IT | SPRAY IT | FINISH IT

### SPRAY SOME PEARL SHINE TO YOUR INTERIOR

Generally speaking, when applied by hand, the plaster application is a labor intensive process. ProPlaster One Coat is also designed to use with worm pump spray machines, providing a smooth, high quality finish onto wall surface in a fraction of the time of traditional plastering methods. This improves productivity enables projects to be handed over earlier.



PRODUCT SPECIFICATIONS	PROFILLER™ ONE COAT
APPEARANCE	White Powder
WORKABILITY	Final setting time before last trowel is 80 minutes
WATER RATIO	Aprox 15 Ltr in a bag of 30 kgs
COMPRESSIVE STRENGTH	Greater than 10.5 MN/m <sup>2</sup> or 1525 psi (pure plaster).
DENSITY	1000 kg/m <sup>3</sup>
COVERAGE	22 – 28 sq/ft bag of 30 kgs (on Cement Blocks)
THERMAL CONDUCTIVITY	0.22W/m.K (i.e. gypsum plaster's insulation is about five times better than cement - sand plaster).
SHELF LIFE	6 months for unopened bag left in dry condition.
PACKAGING:	In 30kg net weight

### MP 25 MIXIT



German Technology

**Application:** One Coat plaster can be applied from 8mm to 25mm thick which can be either machine or hand applied, making ideal for any size of commercial or domestic applications. However, when machine applied it offers excellent productivity and is up to 3 times faster than traditional plastering methods..



UAN: +92-21-111-332-497

A PRODUCT OF  
**LODHIA**  
GYPSUM  
ISO 9001:2008



[WWW.ARISHDRYWALL.COM](http://WWW.ARISHDRYWALL.COM)  
[www.facebook.com/Arishdrywall](https://www.facebook.com/Arishdrywall)